

Climatic conditions for the transport, storage and use of sheet paper on pallets and in rolls

Each unit of the product (roll or pallet) has a label with icons on the left side stating the conditions of storage and usage of the paper.

Transport and storage conditions

Our products are packaged in packaging that ensures the paper retains its moisture under different transport and storage conditions.



Paper in rolls and on pallets must be placed on a dry surface.



Paper in rolls and on pallets must not be exposed to direct weather impacts (rain, snow, sun).

Climatic conditions in the place of use



40-55%
hygro



20-26°C

The recommended relative humidity of the application area for the sheet paper on pallets and in rolls is between 40% and 55%, and the recommended temperature is between 20°C and 26°C.

It is important that the user of the paper ensures that the paper is properly conditioned to ambient temperature before removing the packaging. This ensures that the moisture does not change when the paper is heated or cooled. CAUTION! The packaging must be removed from the roll or pallet by the user when the paper has been fully conditioned to the ambient temperature of the application area. It should be noted that the conditioning time of the unit (roll, pallet) depends on the temperature difference and the size of the unit. For a temperature difference of 10°C, the unit (roll, pallet) needs up to 1 day of conditioning, for a temperature difference of 20°C up to 2 days of conditioning.

If the recommended conditions are not followed, the paper properties may change due to incorrect relative humidity and temperature. In such a case, we cannot grant a claim due to problems with unconditioned paper or the use of paper outside the recommended relative humidity and temperature values for the application area.

For more questions, please contact Technical Customer Support and we will be happy to advise you.

Technical Customer Support